## **Amendments to the Claims:**

Please cancel withdrawn claims 42-43. The following Listing of Claims will replace all prior versions, and listings, of claims in the application:

## **Listing of Claims**

1. (currently amended) A flexible mold for producing a PDP back surface plate comprising: a support and a molding layer disposed on said support;

wherein said molding layer comprises a rib formation surface with a groove pattern having planar portions that connect the grooves with one another and a non-rib region occupying at least a part of a peripheral portion of said rib formation surface wherein the non-rib region at the peripheral portion has a thickness greater than the planar portions that connect the grooves.

- 2. (original) A flexible mold as defined in claim 1, wherein said support and said molding layer are transparent.
- 3. (previously presented) A flexible mold as defined in claim 1, wherein said molding layer is equipped in said rib region with a portion necessary for forming a thin film made of the same material as that of said ribs between adjacent ribs.
- 4. (previously presented) A flexible mold as defined in claim 1, wherein inclination is applied to a terminal portion of each of said groove patterns in said molding layer.
- 5. (previously presented) A flexible mold as defined in claim 1, wherein corners are removed from an upper end portion of a sidewall of said groove pattern.
- 6. (previously presented) A flexible mold as defined in claim 1, wherein said molding layer further includes alignment marks applied to said rib non-formation portion.

Application No.: 10/538450 Case No.: 58343US005

7-19. (cancelled)

20. (currently amended) A PDP back surface plate comprising a substrate having formed thereon a rib pattern layer having a rib region having ribs connected with planar portions having a predetermined shape and a predetermined size and a non-rib region occupying at least a part of a peripheral portion of said rib region, wherein a thin film made of the same material as that of said ribs and planar portions is formed to a predetermined thickness less than the planar portions

21-35 (cancelled)

in said peripheral portion of said non-rib region.

36. (previously presented) The flexible mold of claim 1 wherein the support is made of at least one plastic material selected from the group consisting of polyethylene terephthalate, polyethylene naphthalate, stretched polypropylene, polycarbonate, and triacetate.

37. (previously presented) The flexible mold of claim 1, wherein the molding layer consists of a cured product of a curable material selected from the group comprising a photo-curable (meth)acrylate monomer, a photo-curable (meth)acrylate oligomer, and mixtures thereof.

38. (previously presented) The flexible mold of claim 37, wherein the curable material is selected from the group consisting of urethane acrylate, polyester acrylate and polyether acrylate.

39. (previously presented) The flexible mold of claim 1 wherein the groove pattern is a straight pattern consisting of a plurality of grooves portions arranged substantially in parallel with one another.

40. (previously presented) The flexible mold of claim 1 wherein the groove pattern is a grid pattern.

4

Application No.: 10/538450 Case No.: 58343US005

41. (previously presented) The flexible mold of claim 1, wherein the thickness of the non-rib region is within the range of 5 to 40  $\mu m$ .

41. (previously presented) The flexible mold of claim 1, wherein the groove pattern is chamfered.

42-43. (cancelled)